



LM408e/412e

Superior Performance at Entry Level Prices



Performs best with
Techno
THERM
Labels & Ribbons

Streamlined Features

- Outstanding Value
- All Metal Chassis
- 4.1" Print Width
- Linear & 2-D Symbolologies
- 8.6" OD Label Roll Capacity
- 6 ips Print Speed
- 203 or 305 dpi Models
- Quick, Load & Go Consumable Design

Industry Verticals

- Logistics
- Manufacturing
- Distribution
- Pharmaceutical & Healthcare
- Retail
- Transportation
- Apparel
- Automotive
- Military/DoD

Industry Applications

- Shipping Labels
- Compliance Labeling
- Specimen Labels
- Pharmacy Labels
- Product ID Labeling
- Ticketing & Tags
- Cross Dock Labels
- Inventory Control
- Asset Management

General Specifications

LM408e/412e

PRINTER MODEL		LM408e	LM412e
PRINT SPECIFICATIONS			
Print Method		Direct Thermal, Thermal Transfer	
Print Resolution		203 dpi (8 dot/mm)	305 dpi (12 dot/mm)
Print Speed		Up to 6 ips ¹	
Max. Print Area		4.1" (104 mm) W x 49" (1,245 mm) L	4.1" (104 mm) W x 32" (813 mm) L
MEDIA SPECIFICATIONS			
Sensor Type		Reflective Sensor (for use with pre-printed I-marks) Adjustable See-Through Sensor (for die-cut label with gap)	
Media Type		Roll and Fanfold	
Media Size	Width	0.866" (22 mm) - 5.04" (128 mm)	
	Length	0.237" (6 mm) - 49" (1,245 mm) L	0.237" (6 mm) - 32" (813 mm) L
	Thickness	0.003" (0.08 mm) - 0.010" (0.26 mm)	
	Outer Diameter	8.6" (218.44 mm)	
	Inner Diameter	3" (76.2 mm)	
	Wind Orientation	Face-in	
Ribbon	Size	Max. 4.37" (111 mm) W x 1476' (450 m) L	
	Wind Orientation	Face-in	
FONT / SYMBOLOGIES			
Font		XU, XS, XM, XB, XL, OCR-A, OCR-B	
Barcode Symbologies	Linear	UPC-A, UPC-E, EAN-8, EAN-13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet™, GS1-128, GS1-DataBar™	
	2-Dimensional	PDF417, Micro PDF417, Truncated PDF417, Maxicode™, Data Matrix, QR Code, Composite Symbology	
COMMUNICATION INTERFACE			
Interface Options		Parallel IEEE1284, High-Speed RS232C Serial, Ethernet, 802.11g Wireless, USB	
OPERATING CHARACTERISTICS			
Power Requirements		100-120 / 200-240 Volt AC (<i>Jumper switch required</i>)	
Environment	Operating	41° to 104°F (5° to 40°C), 30-80% RH, non-condensing	
	Storage	23° to 140°F (-5° to 60°C), 30-90% RH, non-condensing	
Dimension		10.67" (271 mm) W x 16.92" (430 mm) D x 12.64" (321 mm) H	
Weight		28.66 lbs. (13 kg)	
OPERATIONAL FEATURES			
Firmware Features		Status Report, Graphic, Sequential Numbering, Form Overlay, Custom Designed Character, Font Decoration, Reverse Image, Line Print, Hex Dump Print, Format Store, Outline, Outline Variation, Label Skip, Zero Slash Switch-Over	
Self Diagnosis Tools		Head Check, Paper End, Ribbon End, Ribbon Near End ² , Head Open, Test Print	

¹ Print speeds available depend on the print resolution and media used.

² Ribbon near-end can be detected with 30 - 15 m of ribbon remaining.



PALCO
Industrial Marking and Labeling, Inc.

www.palcosys.com

11490 South 153rd Street • Omaha, NE 68138
Phone: (402) 556-7000 • Toll Free: (800) 255-7252 • FAX: (402) 556-6622

©2011 SATO America, Inc. All rights Reserved. Rev B • Specifications subject to change without notice • Any unauthorized reproduction of the contents of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.