

ColorWorks C3500 Color Label Printer

Contact Us 1-800-947-8247 x1

Q ZOOM IN



With Epson's ColorWorks C3500 inkjet label printer, you can dramatically reduce label costs, increase operational efficiencies and print high-quality, durable labels on demand in four colors (CMYK) at speeds of up to 4 inches/second.

Model: C31CD54011

Mail-in Rebate

- Ideal for high-mix, low-volume applications
- Compact, robust design for commercial use
- High print speed of up to 4 inches/second
- High-quality four-color inkjet printing
- Individual ink cartridges for efficient use of ink
- Supports all major label applications
- Easily adjusts to handle 1.2" to 4.4" widths
- Rear-feed capability for fanfold and large rolls
- Meets BS5609 certification for GHS labels
- USB and Ethernet interfaces

What's In The Box:

- ColorWorks C3500
- AC power adapter with line cord
- Full capacity Ink cartridges
- Sample label roll
- Media output tray
- Instruction sheet
- CD with utilities and manuals

Print Other:

Printing Technology:

MicroPiezo® inkjet technology, Automatic NozzleChecking

Print Resolution:

- Speed Mode: 360 dpi x 360 dpi
- Quality Mode: 720 dpi x 360 dpi

Print Width:

4.1" (104mm) max.

Print Speed:

- High-speed mode: 360 dpi x 180 dpi
 - 2.7"/sec. (4.1" print width)
 - 3.3"/sec. (2.8" print width)
 - 3.7"/sec. (2.2" print width)
- Fine mode: 360 dpi x 360 dpi
 - 1.4"/sec. (4.1" print width)
 - 1.7"/sec. (2.8" print width)
 - 1.9"/sec. (2.2" print width)

Ink:

Ink Type:

Pigmented ink, individual CMYK cartridges¹

Ink Configuration:

- GJIC22P(C) Cyan C33S020581
- GJIC22P(K) Black C33S020577
- GJIC22P(M) Magenta C33S020582
- GJIC22P(Y) Yellow C33S020583

General:

Operating Systems:

- Windows® XP 32-bit (SP3)/64-bit (SP2)
- Windows Vista® 32-bit/64-bit (SP2)
- Windows 7 32-bit/64-bit (SP1)
- Windows 8 32-bit/64-bit

Temperature:

- Operating: 10-35 degrees C
- Storage: -20-40 degrees C

Humidity:

- Operating: 20-80% RH humidity
- Storage: 5-85% RH humidity

Sound Level:

Approx. 58 dBA

Dimensions:

- Printer: 12.2" x 11.1" x 10.3" (W x D x H)
- Shipping: 17.5" x 15.5" x 16.8" (W x D x H)

Weight:

- Printer (without ink): 26 lbs (12.2 kg)
- Shipping: 41 lbs (12.2 kg)

Safety Approvals:

- EMI: FCC / ICES-003 Class B
- Safety standards: UL60950-1/CSA C22.2 No.60950-1
- Warranty: One year depot repair

Fonts:

Barcode:

UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1DataBar Omnidirectional, GS1 DataBar Truncated, GS1DataBar Limited, GS1 DataBar Expanded, PDF417, QRCode, Maxi Code, GS1 DataBar Stacked, GS1 DataBarStacked Omnidirectional, GS1 DataBar ExpandedStacked, DataMatrix, Aztec Code²

Media Handling:

Width:

- Roll feed: 1.2" – 4.25" (30 – 108mm)
- Fan fold: 2.0" – 4.25" (50 – 108mm)

Type:

Roll-fed or fanfold; die cut or continuous; single layer or adhesive labels on liner; plain paper, fine paper, PETfilm, synthetic

Thickness:

4.7 – 7.5mils (0.12 – 0.19mm)

Roll Diameter:

- O.D. 4.0" (102mm) max.
- Core diameter 1.75" (44mm) to 2.25" (57mm)

Roll-fed Width:

1.2" – 4.25" (30 – 108mm)

Sensors:

Gap, black mark, media cut

Black Mark Size:

Min. 0.20 x 0.16" (5.0 x 4.0mm) (W x H)

Die-cut Label Gap:

Min. 0.12" (3.0mm)

Connectivity:

Standard Connectivity:

USB 2.0 High-speed, Ethernet 10/100 BASE-T

Display Terminal:

Ethernet:

Ethernet 10/100 BASE-T

Power:

Rated Voltage:

AC 100-240 VAC

Rated Frequency:

50-60 Hz

Power Consumption:

- Printing: 30 W (average printing)
- Standby: 2.5 W
- Power Off state: 0.3 W

Power Source:

AC power adapter with line cord