

# ColorWorks C7500 Inkjet Label Printer

Contact Us 1-800-947-8247 x1

Q ZOOM IN



Fast, full-color heavy production ColorWorks C7500 Inkjet Label Printer for Just-In-Time Color™ printing of large print jobs and jobs with tight time windows.

## Label Design Software for C7500

Get a subscription license for CODESOFT for Epson from TEKLYNX. Click here to learn more and get your license.

Model: C31CD84011

✉ Mail-in Rebate

- Reliable performance — rugged design means minimal maintenance and a low overall cost of ownership; ideal for busy, on-demand environments
- Powerful productivity — Just in Time Color printing for high-volume labeling applications
- High-speed, on-demand, color printing — speed through multiple full-color labels with variable data up to 11.8" per second<sup>1</sup>
- Durable labels — BS-5609 certification means labels won't smudge, smear or fade<sup>2</sup>
- Low cost of labeling — up to 50 percent lower printing cost than with laser and thermal transfer printers for high-durability color labels<sup>3</sup>
- Seamless integration — built-in ESC/Label language means you can use the printer with your existing workflow, and even add color with simple programming extensions
- Astounding image quality — powered by PrecisionCore™ inkjet technology from Epson; delivers precise barcodes and ultra sharp text
- Highly efficient — high-yield ink cartridges mean fewer user interventions and less waste than most thermal transfer printers; easy to change, so there's less downtime

## Print Other:

### Printing Technology:

PrecisionCore TFP® with Nozzle Verification Technology

### Print Resolution:

1200 x 600 dpi

### Print Width:

4.25" / 108mm

### Print Speed:

300mm/s

### Ink:

#### Ink Type:

Pigmented ink, 4 individual CMYK cartridges

#### Ink Configuration:

- SJC26P (C) Cyan C33S020615
- SJC26P (B) Black C33S020614
- SJC26P (M) Magenta C33S020616
- SJC26P (Y) Yellow C33S020617

### General:

#### Operating Systems:

- Windows® 8.1 (32-bit, 64-bit)
- Windows 8 (32-bit, 64-bit)
- Windows 7 SP1 (32-bit, 64-bit)
- Windows Vista® SP2 (32-bit, 64-bit)

#### Server Systems:

- Windows XP SP3 (32-bit)
- Windows Server® 2012 R2
- Windows Server 2012
- Windows Server 2008 R2
- Windows Server 2008 (32-bit, 64-bit)
- Windows Server 2003 R2 (32-bit)

#### Temperature:

- Operating: 5 to 35 °C
- Storage: -20 to 60 °C

#### Humidity:

- Operating: 20 – 80% RH

- Storage: 5 – 85% RH

**Sound Level:**  
55 dBA

**Dimensions:**  
Printer: 15.4" x 23.5" x 15.5" (W x D x H)

**Weight:**  
Printer (without ink): Approximately 37.0 kg (81.57 lb)

**Safety Approvals:**  
UL60950-1/CSA C22.2 No.60950-1

## Fonts:

---

**Barcode:**  
UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBarOmnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded

**Two-dimensional Code Printing:**  
PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, DataMatrix, Aztec Code, MicroPDF417, Micro QR Code

## Media Handling:

---

**Type:**  
Roll-fed or fan fold, die cut; single layer or adhesivelabels on liner; plain paper, fine paper, PET film, synthetic

**Thickness:**  
4.7 – 7.5mils (0.12 – 0.19mm)

**Roll Diameter:**  
8.0" (204mm) max.

**Core Diameter:**  
3" (76mm)

**Roll-fed Width:**  
4.41" (50 -112mm)

**Sensors:**  
Gap, black mark

**Black Mark Size:**  
Min. 1.1" x 0.2" (28mm x 5mm) (W x H)

**Die-cut Label Gap:**  
Min. 0.12" (3.0mm)

## Connectivity:

---

**Standard Connectivity:**  
USB 2.0 High-speed, Ethernet

## Display Terminal:

---

**Ethernet:**  
10/100 BASE-T

## Power:

---

**Rated Voltage:**  
AC 100 – 240 VAC

**Rated Frequency:**  
50 – 60 Hz

- Power Consumption:**
- Printing (average printing): 50 – 60 W
  - Standby: 4.1 – 4.4 W
  - Power Off state: 0.2 – 0.5 W