

PRECISION SHRINK LABELING

The OAL Classic Radiant Heat Tunnel for shrink sleeve label and tamper evident band application from American Film & Machinery is designed for middle, full body, combo packs, and full body and cap shrink applications. OAL Classic is a perfect addition to shrink labeling lines in manufactured goods industries including food and beverage, pharmaceutical, nutraceutical, health and beauty, consumer goods, and chemical products.

EFFICIENT OPERATION

The OAL Classic Electric Heat Shrink Tunnel is a versatile and accurate recirculating heat tunnel with high efficiency blowers, adjustable heater element locations, and digital time proportional temperature control with a solid state contactor. The adjustable IR heater element locations allow the tunnel to be set up for a wide variety of applications. The OAL Classic provides optimal shrink control and high quality finish on a number of films including PVC, PETG, OPS, and PLA.

CONSTRUCTED FOR YOUR ENVIRONMENT

Designed to work as an integral part of your day-to-day packaging operations, the OAL Classic tunnel is constructed from rugged stainless steel and supplied with an electrically adjustable stainless steel stand. Motorized height control makes installation easy and can be completed in minutes using standard tools to have you up and running, saving

your company money and increasing your ROI. Due to its versatility and reliability, the OAL Classic Electric Heat Tunnel is also ideal for the changing needs of contract packagers.

DESIGNED TO PERFORM

The OAL Classic utilizes a 940mm x 150mm x 200mm tunnel opening to accommodate a number of shrink sleeve applications. The tunnel has a maximum temperature of 400°F and features high quality IR radiant heating elements for efficient uniform heat distribution. Changing containers or labels create no problems, air controls and adjustments are done from the operator side of the tunnel, making adjustments safe, quick and easy.

THE RIGHT CHOICE

Rugged design. Maximum uptime. Lower cost of ownership. Your benefits go on and on. When it comes to shrink sleeve and tamper band application, rely on American Film & Machinery to provide the right solution for your shrink sleeve labeling needs.















1. Operator Controls

The Operator side controls are conveniently placed for ease of adjustment

2. **Dual Air Flow Blowers**

Two independent air flow motors maximize consistent film shrink

3. Radiant Heat Tunnel

High quality radiant heating elements provide uniform heat distribution to ensure a quality finish

4. Motorized Height Adjustment

Motorized height control makes installation quick and easy; setup and changeover can be completed in minutes

TECHNICAL SPECIFICATIONS	0AL 36	OAL 48
Power	220V/3ph/35A or 480V/3ph/20A; 50/60 Hz	3 Phase 240/480V 50/60Hz
Film Thickness	0.035mm - 0.07mm	0.035mm - 0.07mm
Motor	AC 1/2 x 2	AC 1/2 x 2
Machine Dimensions	800mm (W) x 900mm (L) x 1480mm (H) 31.5" (W) x 35.4" (L) x 58.2" (H)	800mm (W) x 1250mm (L) x 1473mm (H)* 31.5" (W) x 49.3" (L) x 58" (H)*
Tunnel Dimensions	150mm (W) x 940mm (L) x 230mm (H) 5.9" (W) x 37" (L) x 9" (H)	152mm (W) x 1250mm (L) x 230mm (H)* 6" (W) x 49.3" (L) x 9" (H)*
Temperature	400°F	400°F

^{*} XL models available to accommodate wider and taller products. Please inquire about the XL models from your Authorized Distributor or AFM Representative.

Make your products stand out among the competition with AFM Shrink Sleeves and Tamper Evident Banding









A MERICAN FILM & MACHINERY ® ©2022 American Film & Machinery. Specifications subject to change. All trademarks are the property of their respective owners. Product samples shown illustrater the bar of a trademark of the companies.





