



World Class Printing Systems for Real World Applications



MORE OPTIONS FOR MAKING YOUR MARK

Squid Ink's SQ-10 laser coding system is designed for high speed food and beverage, pharmaceutical, cosmetic, and other primary coding applications. Squid Ink CO₂ lasers can permanently mark onto paper, cardboard, plastic, and more.

APPLICATION VERSATILITY

- Permanent coding of text, time and date, bar codes, serial numbering and more
- Quick and easy installation for both stationary and moving products
- Easily fits into production environments where space is limited
- \bullet Laser head can be rotated 90° in less than 5 minutes

RELIABLE AND ECONOMICAL

- No ink/consumables for lower cost of ownership
- Clean and eco-friendly coding system
- Rugged cast aluminum controller body
- IP54 rating ensures maximum reliability and uptime in demanding applications
- Integrated key switch and interlock relay for increased safety on the production floor
- •

HIGH QUALITY CODE GENERATION

- Scribing technology produces non-dot matrix, razor sharp marks on a variety of substrates
- Ability to mix different fonts and logos in a single message
- Discrete coding ability for anti-counterfeiting and traceability
- Ideal coding alternative where CIJ systems are not practical

EASY TO START, SIMPLE TO RUN

- All-in-one design for fast installation and line changes
- Easy to use touchscreen software built right into controller
- Optional 10" touchscreen controller for remote system programming where space is limited
- Intuitive system includes focus finder and code area preview window on product during setup; enables initial laser marking setup within minutes
- Easily configurable in a variety of angles with optional mobile stand
- Optional fume extraction systems available that connect directly to SQ-Laser systems

THE RIGHT SOLUTION

Rugged design. High quality coding. Low cost of ownership. Your benefits go on and on. When it comes to industrial laser coding, rely on Squid Ink to provide the right solution for your coding and marking needs.





1) An optional heavy duty stand is available to simplify setup and install the system in a variety of configurations. **2)** The laser head can be rotated 90 degrees in less than 5 minutes.







Print Trigger - Optical, fiber optic, ultrasonic, laser, metal proximity,

Mobile Stands - Heavy duty stand with ability to rotate laser controller

in any direction and easily raise and lower marking machine by a single

90 Degree Head Pivot Extension - Mirror assembly that allows marking

Hand Held 10" Touchscreen Controller - Allows complete control of

Installation and Training - On-site installation and training available

the system when access is limited due to mounting requirements **Laser Fume Extraction Systems -** SQ-LFX or SQ-LFX PVC for the proper

CE

©2022 Squid Ink Manufacturing, Inc. Specifications subject to change. All trademarks are the property of their

Encoder - For operation with variable speed conveyors

head to point lens in line with unit axis

extraction of laser application fumes

DANGER

SIBLE AND/OR INVISIBLE LASER RADIATIO AVOID EYE OR SKIN EXPOSURE T DIRECT OR SCATTERED RADIATIO

operator; includes casters for easy transportation within plant



3) Easy to use touchscreen software is built right into the controller.

OPTIONAL ACCESSORIES

capacitive proximity

•

•

.

.

4) An optional 10" touchscreen controller allows system programming in limited space environments.

SYSTEM SPECIFICATIONS

- Print Technology CO2 laser coding system, full sealed RF-excited
 metal tube
- Laser Wavelength 10.6µm
- Laser Galvanometer High-precision 2D high-speed scanning galvanometers
- Cooling Method Atmospheric air-cooled
- Dust Way Sealed
- Power Consumption 500W-1000W (110VAC, 60Hz)
- Marking Focal Length 100mm 190mm
- Positioning Accuracy 0.01mm
- Minimum Line Width 0.1mm
- Marking Area 50mm X 50mm 175mm X 175mm
- Assembly Line Speed Support <120m/min
- Marking Speed 800 1000 characters/second
- Character Size Adjustable in marking range
- Marking Line Number Code Rotation 0 to 360°
- Software Features Counter, lot counter shift code, time and date, expiration date, 2D and linear bar codes
- Safety Features Integrated key switch and interlock relay included for safety on the production floor; customer provided shielding necessary to prevent eye or skin exposure
- **Operating Languages -** English and Chinese
- Cabinet Construction Heavy duty cast aluminum
- Cabinet Dimensions 29" (74cm) L x 6.25" (16cm) W x 7.25" (19cm) H
- Electrical Requirements 90 240 VAC, 50/60Hz
- Operating Environment 40°F 105°F (5°C 40°C)
- Humidity Range 10 90% relative humidity, non-condensing
- Packaged Weight 56 lbs. (25kg)

SQUID





TAGE aconologias corportation